

UL 752 Listed and Labeled Levels 1, 2, & 3

Product Features

Construction:	Fully bonded multi-layer ballistic core		
Core:	Laminated multi-layer		
Door Thickness:	Non-Fire rated	1 3/4"	
	20 Minute Fire Rated	1 3/4"	
Max size non-fire rated:	Single	4/0 x 10/0	
	Pair	8/0 x 10/0	
Max size 20 min fire rated:		<u>Neutral Pressure</u>	<u>Positive Pressure "B"</u>
	Single (20 minute)	4/0 x 10/0	4/0 x 10/0
	Pair (20 minute)	8/0 x 10/0	8/0 x 10/0
	All pairs require a Protect BR Metal Edge / Astragal		
Stiles:	1/2" Stiles prior to factory sizing with matching banded edges		
Faces:	All veneer species, plastic laminates, MDO		
Cross bands:	High density fiberboard (HDF)		
Adhesives:	Type 1 (waterproof)		
Lite Openings:	UL 752 listed frame and glass (must be factory installed). Minimum 6" top rail; 12" bottom rail, 6" hinge stile, 8" lock stile.		
Machining/Finishing:	Prefit, bevel, & factory machining (required) and factory finishing available. (Contact Sales for Machining restrictions)		
Hardware:	Minimum requirement BHMA 1, 2, 3 mortise locks or BHMA 2 cylinder locks. Doors with raceways will include factory installed wires.		
Warranty:	Limited three (3) year - Warranty does not apply to exterior applications		
Labeling Approvals:	Bullet Resistance: Underwriters Laboratories (File # BP10714)		
Fire:	Guardian Fire Testing Laboratories		
Specifications:	Meets UL 752, WDMA & AWI quality standards (contact Sales for label approvals)		
Environmental/LEED Options:	MR4-Recycled content/MR5-Regional Materials/MR6-Rapidly renewable/ MR7 Certified Wood/IEQ4.4-Low-emitting materials (NAUF)		