

### Non-Rated

#### Product Features

<b>Construction:</b>	All Non-Rabbeted Wicket Doors are constructed by cutting the Wicket (inner) Door out of the Main (outer) door. A hardwood 5/8" thick frame is installed as a liner around the cut out for the Wicket using Stainless Steel screws (heads exposed). The 5/8" thick frame can be machined for a wide variety of hinges and locks. On finished or plastic laminate doors the frame is stained or painted to match. Custom options are available upon request.	
<b>Core:</b>	Structural composite lumber core (SCL)	
<b>Door Thickness:</b>	Standard	1 3/4"
<b>Maximum Size:</b>	Single	4/0 x 10/0
	Pair	8/0 x 10/0
<b>Stiles:</b>	(Main Door) 7/8" matching hardwood prior to factory trimming (other options available) (Wicket) SCL banded to match faces	
<b>Faces:</b>	All veneer species, medium density overlay (MDO), plastic laminate	
<b>Veneer Matching:</b>	Available in pairs, sets, & transoms (special matching available)	
<b>Cross Bands:</b>	High density fiberboard (HDF)	
<b>Adhesives:</b>	Type 1 (waterproof)	
<b>Max Lite Openings:</b>	(In the Wicket Door) Must maintain minimum of 8" on stile edges 6" top and bottom.	
<b>Machining/Finishing:</b>	Prefit, bevel, & complete factory machining and factory UV finishing available	
<b>Warranty:</b>	Limited one year (1)	
<b>Specifications:</b>	Meets WDMA & AWI quality standards	
<b>Environmental/LEED Options:</b>	MR4-Recycled content/MR6-Rapidly renewable/IEQ4.4-Low-emitting materials (no added urea formaldehyde resins)	