

Non-Listed & Labeled (Bullet Resistance)

Our Non-Listed & Labeled bullet resistant doors are constructed using the same design and materials as our UL 752 Listed & Labeled doors but because of hardware requirements or Bullet Resistance Level they do not conform to our approvals. Hardware preparations that require removal of the center ballistic material will void the bullet protection in the areas removed.

Product Features

Construction:	Fully bonded multi-layer ballistic core
Core:	Laminated multi-layer
Door Thickness:	Varies by level 1 3/4" - 2 1/2"
Max size:	Single 5/0 x 10/0 Pair (levels 1,2 & 3) 10/0 x 10/0 Requires a Protect BR Metal Edge / Astragal
Stiles:	1/2" Stiles prior to factory sizing with matching edges
Faces:	All veneer species, plastic laminates, MDO
Cross bands:	High density fiberboard (HDF)
Adhesives:	Type 1 (waterproof)
Max Lite Openings:	Minimum 6" top rail; 12" bottom rail and 6" hinge stile 8" lock stile
Machining/Finishing:	Prefit, bevel, & factory machining (Factory machining required, some hardware preps may void bullet protection in the prep area) Factory finishing available
Hardware:	Minimum requirement BHMA grade 1, 2, 3, mortise locks or BHMA grade 2 cylinder locks. Doors with raceways will include factory installed wires.
Warranty:	Limited three (3) year up to 4/0 x 10/0 - <i>Warranty does not apply to exterior applications</i>
Labeling Approvals:	Contact Sales for available labeling
Specifications:	WDMA & AWI quality standards (contact sales for label approvals)
Environmental/LEED Options:	MR4-Recycled content/MR5-Regional Materials/MR6-Rapidly renewable/ MR7 Certified Wood/IEQ4.4-Low-emitting materials (no added urea formaldehyde resins)