

Non-Rated

Product Features

Construction:	All Rabbeted Wicket Doors are constructed by cutting the Wicket (inner) Door out of the Main (outer) door. A hardwood 5/8" thick frame is installed as a liner around the cut out for the Wicket using Stainless Steel screws (heads exposed). A 1/2" X 1/2" door stop molding is attached to the liner frame using adhesives and brad nails. The door stop molding can be used on as many edges of the wicket as specified by the customer. The 5/8" thick frame can be machined for a wide variety of hinges and locks. On finished or plastic laminate doors the frame is stained or painted to match. The edges of the wicket door that are to be rabbeted will be fitted with hardwood edges. On finished or plastic laminate doors the edges are stained or painted to match. Custom options are available upon request.	
Core:	Structural composite lumber core	
Door Thickness:	Standard	1 3/4"
Maximum Size:	Single	4/0 x 10/0
	Pair	8/0 x 10/0
Stiles:	(Main Door) 7/8" matching hardwood prior to factory trimming (other options available) (Wicket) SCL banded to match faces	
Faces:	All veneer species, medium density overlay (MDO), plastic laminate	
Veneer Matching:	Available in pairs, sets, & transoms (special matching available)	
Cross Bands:	High density fiberboard (HDF)	
Adhesives:	Type 1 (waterproof)	
Max Lite Openings:	(In the Wicket Door) Must maintain minimum of 8" on stile edges 6" top and bottom.	
Machining/Finishing:	Prefit, bevel, & complete factory machining and factory UV finishing available	
Warranty:	Limited one year (1)	
Specifications:	Meets WDMA & AWI quality standards	
Environmental/LEED Options:	MR4-Recycled content/MR6-Rapidly renewable/IEQ4.4-Low-emitting materials (no added urea formaldehyde resins)	